

2PC VALVES



DM3800/DM3833/V-ball for control valve 15°, 30°, 45°, 60°, 90°, slot, or custom



FSLD3500/FIRE SAFE/2000PSI

2pc Ball Valve, FIRE SAFE 2000psi, 316SS or WCB BODY, 316SS TRIM, FP, GRAPHOIL PACKING, TFM Seats, NPT, with Anti-Static LD Handle



FSLD3900/FIRE SAFE/3000PSI

2PC, Full port Firesafe, 316SS or WCB Body, 316SS Trim, Graphoil Packing, Delrin Seat, Seal Welded ends with NPT ends, locking handle



3700/1000PSI

2pc Ball Valve, 1000psi, CF8M, FP, Teflon Packing and Seats, NPT, with Locking Device

3PC VALVES



DM4500/1000PSI/V-ball for control valve 15°, 30°, 45°, 60°, 90°, slot, or custom



DM4600/FIRE SAFE/2000PSI/V-ball for control valve 15°, 30°, 45°, 60°, 90°, slot, or custom



DM4800/FIRE SAFE/3000PSI/PEEK/METAL SEATED/V-ball for control valve 15°, 30°, 45°, 60°, 90°, slot, or custom



DMCF7300/CAVITY FILLED/TRI-CLAMP/SANITARY

3 pc Sanitary Ball valve, 316SS, Tri Clamp Ends, with PTFE Cavity Filler



6833 STAINLESS STEEL SPRING CHECK VALVE

Check Valve, CF8M, NPT ends, 800 PSI, Teflon seats, Spring Check valve

FLANGED



DM2500/2PC/150#/300#/V-ball for control valve 15°, 30°, 45°, 60°, 90°, slot, or custom

2PC 316SS OR WCB BODY, 316 SS TRIM, FP, 150# FLANGED B16.50, BALL VALVE, ANSI B16.10 FF, LOCKING HANDLE, SELF ADJUSTING STEM PACKING, 275 PSI, ISO 5211



DM9900/SEGMENTED DIRECT MOUNT ANSI CLASS 150# BALL VALVE, 60 DEGREE VBALL, ASMEB16.5 150# FLANGED, WCB BODY, A351 GR CF8M BALL, SS316 STELLITED METAL SEAT, GRAPHITE STEM PACKING, ANSI CLASS IV SHUTOFF, BLOW OUT PROOF STEM ISO DIRECT MOUNT



DM9923FGM-W ANSI600, "segment valve, wafer type, Class 600, WCB with 316 trim, metal seat, Graphite gasket/ packing/60* ball: SS316+Hard surface/ seat: SS316+Stellite seat", Live Loaded Packing, Direct Mount, 60° V Ball