



MHKZ.MH64029 - MANUAL VALVES

Manual Valves

See General Information for Manual Valves

J FLOW CONTROLS

MH64029

4665 INTERSTATE DRIVE

CINCINNATI, OH 45246 USA

Gas shut-off valves, Model(s) Series 2500F for Inert Gases, Fuel Gases, Hydrogen, Nitrogen, Air, LPG, Natural and Manufactured Gases, Kerosene, Fuel Oils 1-6, and Gasoline, sizes 1/2", 3/4", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6" at 275 psi max.(%)

Gas shut-off valves, Model(s) Series DM4600F for Inert Gases, Fuel Gases, Hydrogen, Nitrogen, Air, LPG, Natural and Manufactured Gases, Kerosene, Fuel Oils 1-6, and Gasoline, sizes 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", at 1485 psi max.(%)

(%) - Complementary Listed under YRPV, YSDT, YQNZ, YRBX

Last Updated on 2019-11-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

Cookies on UL

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.. [Learn More](#)

[Cookie Settings](#)[✓ Accept](#)



YQNZ.MH64029 - COMPRESSED GAS SHUTOFF VALVES

Compressed Gas Shutoff Valves

See General Information for Compressed Gas Shutoff Valves

J FLOW CONTROLS

MH64029

4665 INTERSTATE DRIVE

CINCINNATI, OH 45246 USA

Gas shut-off valves, Series DM4600F for Inert Gases, Fuel Gases, Hydrogen, Nitrogen, Air, LPG, Natural and Manufactured Gases, Kerosene, Fuel Oils 1-6, and Gasoline, sizes 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", at 1485 psi max. (%)

Gas shut-off valves, Series 2500F for Inert Gases, Fuel Gases, Hydrogen, Nitrogen, Air, LPG, Natural and Manufactured Gases, Kerosene, Fuel Oils 1-6, and Gasoline, sizes 1/2", 3/4", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6" at 275 psi max. (%)

(%) - Complementary Listed under, YRPV, YSDT, MHKZ, YRBX

Last Updated on 2019-11-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

Cookies on UL

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.. [Learn More](#)

› [Cookie Settings](#)

✓ Accept



YRBX.MH64029 - FLAMMABLE LIQUID SHUTOFF VALVES

Flammable Liquid Shutoff Valves

See General Information for Flammable Liquid Shutoff Valves

J FLOW CONTROLS

MH64029

4665 INTERSTATE DRIVE

CINCINNATI, OH 45246 USA

Gas shut-off valves, Model(s) Series 2500F for Inert Gases, Fuel Gases, Hydrogen, Nitrogen, Air, LPG, Natural and Manufactured Gases, Kerosene, Fuel Oils 1-6, and Gasoline, sizes 1/2", 3/4", 1"-1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6" at 275 psi max. (%)

Gas shut-off valves, Model(s) Series DM4600F for Inert Gases, Fuel Gases, Hydrogen, Nitrogen, Air, LPG, Natural and Manufactured Gases, Kerosene, Fuel Oils 1-6, and Gasoline, sizes 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", at 1485 psi max.(%)

(%) - Complementary Listed under YRPV, YSDT, MHKZ, YQNZ

Last Updated on 2019-11-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

Cookies on UL

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.. [Learn More](#)

[> Cookie Settings](#)

[✓ Accept](#)



YRPV.MH64029 - GAS SHUTOFF VALVES

Gas Shutoff Valves

See General Information for Gas Shutoff Valves

J FLOW CONTROLS

MH64029

4665 INTERSTATE DRIVE

CINCINNATI, OH 45246 USA

Gas shut-off valves, Series DM4600F for Inert Gases, Fuel Gases, Hydrogen, Nitrogen, Air, LPG, Natural and Manufactured Gases, Kerosene, Fuel Oils 1-6, and Gasoline, sizes 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", at 1485 psi max. (%)

Gas shut-off valves, Series 2500F for Inert Gases, Fuel Gases, Hydrogen, Nitrogen, Air, LPG, Natural and Manufactured Gases, Kerosene, Fuel Oils 1-6, and Gasoline, sizes 1/2", 3/4", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6" at 275 psi max. (%)

(%) - Complementary Listed under, YSDT, MHKZ, YQNZ,YRBX

Last Updated on 2019-11-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

Cookies on UL

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.. [Learn More](#)

[➤ Cookie Settings](#)[✓ Accept](#)



YSDT.MH64029 - LP-GAS SHUTOFF VALVES

LP-Gas Shutoff Valves

See General Information for LP-Gas Shutoff Valves

J FLOW CONTROLS

MH64029

4665 INTERSTATE DRIVE

CINCINNATI, OH 45246 USA

Gas shut-off valves Model(s) Series 2500F, sizes 1/2", 3/4", 1*1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6" at 275 psi max. (%)

Series DM4600F, sizes 1/4", 3/8", 1/2", 3/4", 1", 1-1/4", 1-1/2", 2", at 1485 psi max. (%)

(%) - Complementary Listed under YRPV, MHKZ, YQNZ, YRBX

Last Updated on 2019-11-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

Cookies on UL

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners.. [Learn More](#)

[› Cookie Settings](#)[✓ Accept](#)